









Griglie stradali

Altezza regolabile progressivamente **Sistema focus**
con zoccolo in cemento

secondo la norma VSS-Norm

Figura no.							
	a livello	a livello	inclinato	a livello	a livello	a livello	a livello
 D400 VSS 870 cm ² / 1850 l/min	203-102-a livello	203-102, Ø1050-a livello	203-103-inclinato	203-103-a livello	203-103, Ø1050-a livello	203-104-a livello	203-105-a livello
 D400 VSS 808 cm ² / 1800 l/min	205-102-a livello	205-102, Ø1050-a livello	205-103-inclinato	205-103-a livello	205-103, Ø1050-a livello	205-104-a livello	205-105-a livello
 D400 VSS 885 cm ² / 1900 l/min	210-102-a livello	210-102, Ø1050-a livello	210-103-inclinato	210-103-a livello	210-103, Ø1050-a livello	210-104-a livello	210-105-a livello
 100 kN VSS 902 cm ² / 1950 l/min	215-102-a livello	215-102, Ø1050-a livello	215-103-inclinato	215-103-a livello	215-103, Ø1050-a livello	215-104-a livello	215-105-a livello
 C250 VSS 780 cm ² / 1750 l/min	220-102-a livello	220-102, Ø1050-a livello	220-103-inclinato	220-103-a livello	220-103, Ø1050-a livello	220-104-a livello	220-105-a livello

Aperture delle fessure / Capacità raccolta d'acqua

Coperchio provvisorio: figura no 203 – 225 HD